

Dry Film Measurement

ALSO AVAILABLE

Complies with the requirements of AS3894.3 -1993

Australian Zero Plates

Ferrous or
Non-ferrous


Available in
35 x 35mm,
43 x 43mm and
75 x 75mm sizes



Measured Calibration Films

Working or Certified sets are available
in various sizes from 2 μ m to 12.5mm
(as below)

2, 4, 6, 8, 10, 12, 19, 25, 30, 35, 50, 75, 100,
125, 190, 250, 350, 400, 500, 1000, 1500,
3000, 4500, 6000, 1000, 12500 μ m



Proudly Manufactured in Australia by PCWI

PCWI CROSS HATCH CUTTERS

Complies with the requirements of ASI580 Method 408.1, BS3900-E6, ASTM 3359-B, DIN53-151 and ISO 2409.

For measuring adhesion of a wide range of coatings,
including films, varnishes and paints from either single
or multi-coat applications.

Manufactured
by PCWI



Three cutters are available:



PCWI CALIBRATION BLOCKS

A series of individual steel blocks for checking the
linearity of ultrasonic thickness gauges and flaw
detectors.

Features

Supplied with certification traceable to NATA/
UKAS/NIST Certified Equipment.

Each block is corrosion protected by flash coating
to stop surface rusting.

Measured to 0.0001mm

Supplied in a sturdy PVC case.

Sizes: 1.5mm, 2.5mm, 5mm, 8mm, 10mm,
15mm, 20mm, 25mm and 50mm

Tolerance: -0.000mm to +0.01mm

Diameter: 20mm

Manufactured
by PCWI

