

TORQUE WRENCHES Dial Type



CLASSIC Series Dual Scale English & Newton Meter

The CLASSIC Series continues to offer a body design that provides durability and performance. Torque capacities range from 15 in. lbs. to 2,000 ft. lbs., in 1/4", 3/8", 1/2", 3/4" and 1" drives.

FEATURES:

- Sturdy body construction insures durability
- Easy to Read Laser Marked Dual Scale
- Large easy to read dial is shock resistant and protected by a tough metal guard
- Memory needle retains highest torque reading applied
- Calibrated in both CW and CCW direction
- Accuracy +/- 2%, from 20-100% of full scale
- Individually serialized with matching certificate of calibration traceable to N.I.S.T.



Part Number	Torque Range English	Incr.	Torque Range Newton Meter	Incr.	Drive Size	A In. (mm)	B In. (mm)	C In. (mm)	D In. (mm)	Wt. Lbs. (Kg)
INCH POUND										
151LDIN	0-15 in. lb.	.25 in. lb.	0-18 dNm	.25dNm	1/4"	10 (254)	1.12 (28.58)	2.12 (53.98)	2.75 (69.85)	1 (.45)
301LDIN	0-30 in. lb.	.5 in. lb.	0-3.5 Nm	.1 Nm	1/4"	10 (254)	1.12 (28.58)	2.12 (53.98)	2.75 (69.85)	1 (.45)
751LDIN	0-75 in. lb.	1 in. lb.	0-9 Nm	.2 Nm	1/4"	10 (254)	1.12 (28.58)	2.12 (53.98)	2.75 (69.85)	1 (.45)
752LDIN	0-75 in. lb.	1 in. lb.	0-9 Nm	.2 Nm	3/8"	10 (254)	1.12 (28.58)	2.25 (57.15)	2.75 (69.85)	1 (.45)
1502LDIN	0-150 in. lb.	2 in. lb.	0-18 Nm	.5 NM	3/8"	10 (254)	1.12 (28.58)	2.25 (57.15)	2.75 (69.85)	1 (.45)
2502LDIN	0-250 in. lb.	5 in. lb.	0-30 Nm	.5 Nm	3/8"	10 (254)	1.12 (28.58)	2.25 (57.15)	2.75 (69.85)	1 (.45)
3002LDIN	0-300 in. lb.	5 in. lb.	0-35 Nm	1 Nm	3/8"	10 (254)	1.12 (28.58)	2.25 (57.15)	2.75 (69.85)	1 (.45)
6002LDIN	0-600 in. lb.	10 in. lb.	0-70 Nm	2 Nm	3/8"	14.88 (378)	1.50 (38.10)	2.25 (57.15)	2.75 (69.85)	1.75 (.79)